

BELT CARE Riemenversiegelung

Revision date: 21.05.2024

Page 1 of 13

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

BELT CARE Riemenversiegelung

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

see product name

1.3. Details of the supplier of the safety data sheet

Company name: Atlantic Mineralölwerk GmbH
Street: Veerenkamp 25
Place: D-21739 Dollern
Telephone: 0049-(0)4163-81590
E-mail: info@atlantic-oel.de
Contact person: Analysis
E-mail: info@atlantic-oel.de
Internet: www.atlantic-oel.de

1.4. Emergency telephone number:

0049-(0)4163-81590

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No 1272/2008**

Aerosol 1; H222-H229
Asp. Tox. 1; H304
STOT SE 3; H336
Aquatic Chronic 2; H411

Full text of hazard statements: see SECTION 16.

2.2. Label elements**Regulation (EC) No 1272/2008****Hazard components for labelling**

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Signal word: Danger**Pictograms:****Hazard statements**

H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.

according to Regulation (EC) No 1907/2006

BELT CARE Riemenversiegelung

Revision date: 21.05.2024

Page 2 of 13

P251	Do not pierce or burn, even after use.
P271	Use only outdoors or in a well-ventilated area.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of contents/container to in accordance with local/regional/national/international regulation.

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

In case of insufficient ventilation and/or through use, explosive/highly flammable mixtures may develop.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Relevant ingredients**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
106-97-8	butane			45 - < 50 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Liquefied gas; H220 H280			
	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane			25 - < 30 %
	926-605-8		01-2119486291-36	
	Flam. Liq. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H336 H304 H411 EUH066			
74-98-6	propane			20 - < 25 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1, Liquefied gas; H220 H280			
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics			1 - < 2.5 %
	920-750-0		01-2119473851-33	
	Flam. Liq. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H225 H336 H304 H411 EUH066			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
	926-605-8	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	25 - < 30 %
	inhalation: LC50 = 73860 mg/l (vapours); oral: LD50 = >5000 mg/kg		
	920-750-0	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	1 - < 2.5 %
	inhalation: LC50 = > 23,3 mg/l (vapours); dermal: LD50 = > 2800 - 3100 mg/kg; oral: LD50 = >5000 mg/kg		

SECTION 4: First aid measures**4.1. Description of first aid measures****General information**

When in doubt or if symptoms are observed, get medical advice.
If medical advice is needed, have product container or label at hand.

After inhalation

Provide fresh air. If breathing is irregular or stopped, administer artificial respiration. In case of respiratory tract irritation, consult a physician.

BELT CARE Riemenversiegelung

Revision date: 21.05.2024

Page 3 of 13

After contact with skin

Take off contaminated clothing and wash it before reuse. After contact with skin, wash immediately with plenty of water and soap. In case of skin irritation, consult a physician.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of eye irritation consult an ophthalmologist.

After ingestion

Observe risk of aspiration if vomiting occurs. If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

Water spray jet, Carbon dioxide (CO₂), Foam, Extinguishing powder.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol. Pressurized container: May burst if heated. Vapours can form explosive mixtures with air.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General advice**

Remove all sources of ignition. Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

For non-emergency personnel

Ventilate affected area. Remove persons to safety. Do not breathe aerosol.

For emergency responders

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk.

6.3. Methods and material for containment and cleaning up**For containment**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents).

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Safe handling: see section 7

according to Regulation (EC) No 1907/2006

BELT CARE Riemenversiegelung

Revision date: 21.05.2024

Page 4 of 13

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Do not pierce or burn, even after use. If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Do not spray on naked flames or any incandescent material. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

Further information on handling

Heating causes rise in pressure with risk of bursting.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaustion at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances.

7.3. Specific end use(s)

No information available.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

BELT CARE Riemenversiegelung

Revision date: 21.05.2024

Page 5 of 13

DNEL/DMEL values

CAS No	Name of agent			
DNEL type		Exposure route	Effect	Value
	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane			
Worker DNEL, long-term		inhalation	systemic	5306 mg/m³
Worker DNEL, long-term		dermal	systemic	13964 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	1131 mg/m³
Consumer DNEL, long-term		dermal	systemic	1377 mg/kg bw/day
Consumer DNEL, long-term		oral	systemic	1301 mg/kg bw/day
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics			
Worker DNEL, long-term		dermal	systemic	773 mg/kg bw/day
Worker DNEL, long-term		inhalation	systemic	2035 mg/m³
Consumer DNEL, long-term		dermal	systemic	699 mg/kg bw/day
Consumer DNEL, long-term		inhalation	systemic	608 mg/m³
Consumer DNEL, long-term		oral	systemic	699 mg/kg bw/day

Additional advice on limit values

To date, no national critical limit values exist.

8.2. Exposure controls**Appropriate engineering controls**

Do not breathe gas/fumes/vapour/spray. If local exhaust ventilation is not possible or not sufficient, the entire working area should be ventilated by technical means.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Wear eye protection/face protection. Suitable eye protection: Eye glasses with side protection EN 166

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

Suitable material: NBR (Nitrile rubber) (0,4 mm) EN ISO 374

Breakthrough time: >=480 min

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear anti-static footwear and clothing

Respiratory protection

In case of inadequate ventilation wear respiratory protection. Suitable respiratory protection apparatus: Combination filtering device A-P2.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid
Colour:	transparent - whitish
Odour:	like: Solvent

Test method

BELT CARE Riemenversiegelung

Revision date: 21.05.2024

Page 6 of 13

Melting point/freezing point:	not applicable
Boiling point or initial boiling point and boiling range:	< -20 °C
Flammability:	not determined
Lower explosion limits:	0,6 vol. %
Upper explosion limits:	10,9 vol. %
Flash point:	< -20 °C
Auto-ignition temperature:	260 °C
Decomposition temperature:	not determined
pH-Value:	not applicable
Viscosity / kinematic:	not determined
Water solubility: (at 20 °C)	practically insoluble
Solubility in other solvents	not determined
Partition coefficient n-octanol/water:	not determined
Vapour pressure:	not determined
Density (at 20 °C):	0,6 g/cm ³ calculated.
Relative vapour density:	not determined
Particle characteristics:	not applicable

9.2. Other information**Information with regard to physical hazard classes****Explosive properties**

Heating may cause an explosion.

Oxidizing properties

not determined

Other safety characteristics

Evaporation rate:	not determined
Solid content:	not determined
Viscosity / dynamic:	not applicable

SECTION 10: Stability and reactivity**10.1. Reactivity**

Extremely flammable aerosol. Pressurized container: May burst if heated.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames. Vapours can form explosive mixtures with air.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

BELT CARE Riemenversiegelung

Revision date: 21.05.2024

Page 7 of 13

Acute toxicity

Based on available data, the classification criteria are not met.

ATEmix calculated

ATE (oral) > 2000 mg/kg; ATE (dermal) > 2000 mg/kg; ATE (inhalation vapour) > 20 mg/l; ATE (inhalation dust/mist) > 5 mg/l

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane				
	oral	LD50 >5000 mg/kg	Rat	OECD 401	
	inhalation (4 h) vapour	LC50 73860 mg/l	Rat	Publication (1970)	OECD Guideline 403
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics				
	oral	LD50 >5000 mg/kg	Rat		
	dermal	LD50 > 2800 - 3100 mg/kg	Rat	Study report (1977)	The acute toxicity of SBP 100/140 was de
	inhalation (4 h) vapour	LC50 > 23,3 mg/l	Rat	Study report (1988)	OECD Guideline 403

Irritation and corrosivity

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Repeated exposure may cause skin dryness or cracking.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2. Information on other hazards**Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

Further information

The mixture is classified as hazardous according to regulation (EC) No 1272/2008 [CLP]. No further relevant information available.

SECTION 12: Ecological information**12.1. Toxicity**

Toxic to aquatic life with long lasting effects.

BELT CARE Riemenversiegelung

Revision date: 21.05.2024

Page 8 of 13

CAS No	Chemical name						
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method	
	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane						
	Acute fish toxicity	LL50	12 mg/l	96 h	Oncorhynchus mykiss	Study report (1994)	OECD Guideline 203
	Acute algae toxicity	ErC50 mg/l	7,276	72 h	Raphidocelis subcapitata	Company report (2009)	The aquatic toxicity was estimated by a
	Acute crustacea toxicity	EL50 mg/l	17,06	48 h		Company report (2009)	The aquatic toxicity was estimated by a
	Fish toxicity	NOEC mg/l	2,187	28 d	Oncorhynchus mykiss	Company report (2009)	The aquatic toxicity was estimated by a
	Crustacea toxicity	NOEC mg/l	3,818	21 d		Company report (2009)	The aquatic toxicity was estimated by a
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics						
	Acute fish toxicity	LL50 mg/l	3 - 10	96 h	Oncorhynchus mykiss	Study report (1995)	OECD Guideline 203
	Acute algae toxicity	ErC50	12 mg/l	72 h	Raphidocelis subcapitata	SIDS Initial Assessment Report For SIAM	OECD Guideline 201
	Acute crustacea toxicity	EL50	7,4 mg/l	48 h		SIDS Initial Assessment Report For SIAM	OECD Guideline 202
	Fish toxicity	NOEC mg/l	0,574	28 d	Oncorhynchus mykiss	Hydrocarbon Solvents Consortium SEIF (HS)	The aquatic toxicity was estimated by a
	Algae toxicity	NOEC	(10) mg/l	3 d	Pseudokirchneriella subcapitata		
	Crustacea toxicity	NOEC	1 mg/l	21 d		SIDS Initial Assessment Report For SIAM	OECD Guideline 211

12.2. Persistence and degradability

The product has not been tested.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane			
	Biodegradation	98%	28	
	Readily biodegradable (according to OECD criteria).			
	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics			
	Biodegradation	98%	28	OECD 301F/ ISO 9408/ EEC 92/69/V, C.4-D
	Readily biodegradable (according to OECD criteria).			

12.3. Bioaccumulative potential

The product has not been tested.

according to Regulation (EC) No 1907/2006

BELT CARE Riemenversiegelung

Revision date: 21.05.2024

Page 9 of 13

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
106-97-8	butane	2,89
	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	3,6
74-98-6	propane	2,36

BCF

CAS No	Chemical name	BCF	Species	Source
	Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	>= 35,8		REACH Registration D

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No further relevant information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)****14.1. UN number or ID number:**

UN 1950

14.2. UN proper shipping name:

AEROSOLS

14.3. Transport hazard class(es):

2

14.4. Packing group:

-

Hazard label:

2.1



Classification code:

5F

Special Provisions:

190 327 344 625

Limited quantity:

1 L

Excepted quantity:

E0

according to Regulation (EC) No 1907/2006

BELT CARE Riemenversiegelung

Revision date: 21.05.2024

Page 10 of 13

Transport category: 2
Tunnel restriction code: D

Inland waterways transport (ADN)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
Hazard label: 2.1



Classification code: 5F
Special Provisions: 190 327 344 625
Limited quantity: 1 L
Excepted quantity: E0

Marine transport (IMDG)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
Hazard label: 2.1



Special Provisions: 63, 190, 277, 327, 344, 381, 959
Limited quantity: 1000 mL
Excepted quantity: E0
EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1950
14.2. UN proper shipping name: AEROSOLS, FLAMMABLE
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
Hazard label: 2.1



Special Provisions: A145 A167 A802
Limited quantity Passenger: 30 kg G
Passenger LQ: Y203
Excepted quantity: E0
IATA-packing instructions - Passenger: 203
IATA-max. quantity - Passenger: 75 kg
IATA-packing instructions - Cargo: 203
IATA-max. quantity - Cargo: 150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



Danger releasing substance: Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane

according to Regulation (EC) No 1907/2006

BELT CARE Riemenversiegelung

Revision date: 21.05.2024

Page 11 of 13

14.6. Special precautions for user

Warning: Flammable gases.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28, Entry 40

Directive 2010/75/EU on industrial emissions:	98,05 % (588,3 g/l)
---	---------------------

Directive 2004/42/EC on VOC in paints and varnishes:	98,05 % (588,3 g/l)
--	---------------------

Information according to Directive 2012/18/EU (SEVESO III):	P3a FLAMMABLE AEROSOLS
---	------------------------

Additional information:	E2
-------------------------	----

Additional informationTo follow: 850/2004/EC, 79/117/EEC, 689/2008/EC , 2008/47/EC
Aerosol Directive (75/324/EEC).**National regulatory information**

Employment restrictions:	Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).
--------------------------	--

Water hazard class (D):	2 - obviously hazardous to water
-------------------------	----------------------------------

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 1,2,4,5,6,7,8,9,11,12,14,15.

BELT CARE Riemenversiegelung

Revision date: 21.05.2024

Page 12 of 13

Abbreviations and acronyms

Flam. Gas: Flammable gases
Aerosol: Aerosol
Liquefied gas
Flam. Liq: Flammable liquid
Asp. Tox: Aspiration hazard
STOT SE: Specific target organ toxicity - single exposure
Aquatic Chronic: Chronic aquatic hazard
ADR: Accord européen sur le transport des marchandises dangereuses par Route
(European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
GHS: Globally Harmonized System of Classification and Labelling of Chemicals
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service
LC50: Lethal concentration, 50%
LD50: Lethal dose, 50%
CLP: Classification, labelling and Packaging
REACH: Registration, Evaluation and Authorization of Chemicals
GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals
UN: United Nations
DNEL: Derived No Effect Level
DMEL: Derived Minimal Effect Level
PNEC: Predicted No Effect Concentration
ATE: Acute toxicity estimate
LL50: Lethal loading, 50%
EL50: Effect loading, 50%
EC50: Effective Concentration 50%
ErC50: Effective Concentration 50%, growth rate
NOEC: No Observed Effect Concentration
BCF: Bio-concentration factor
PBT: persistent, bioaccumulative, toxic
vPvB: very persistent, very bioaccumulative
RID: Regulations concerning the international carriage of dangerous goods by rail
ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
(Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)
EmS: Emergency Schedules
MFAG: Medical First Aid Guide
ICAO: International Civil Aviation Organization
MARPOL: International Convention for the Prevention of Marine Pollution from Ships
IBC: Intermediate Bulk Container
VOC: Volatile Organic Compounds
SVHC: Substance of Very High Concern
For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Aerosol 1; H222-H229	On basis of test data
Asp. Tox. 1; H304	Calculation method
STOT SE 3; H336	Bridging principle "Aerosols"
Aquatic Chronic 2; H411	Calculation method

Relevant H and EUH statements (number and full text)

according to Regulation (EC) No 1907/2006

BELT CARE Riemenversiegelung

Revision date: 21.05.2024

Page 13 of 13

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the relevant ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)